

92X92X25 mm

JA0925-0N Series



- **Motor** : Two-pole shaded pole induction motor
- **Frame** : Aluminum Alloy, Painted black
- **Impeller** : Retardant thermoplastic in black color, rated UL94V-0
- **Speed Range** : $\pm 10\%$
- **Impedance protected**

SPECIFICATIONS

| Model | Bearing | Nominal Voltage (V) | Frequency (Hz) | Air Flow (CFM) | Static Pressure (inchH ₂ O) | Speed (R.P.M.) | Nominal Current (Amp) | Input Power (Watt) | Noise (dBA) | Weight (g) |
|-------------|---------|---------------------|----------------|----------------|--|----------------|-----------------------|--------------------|-------------|------------|
| JA0925H1B0N | B | 110 - 120 | 50 | 23.24 | 0.054 | 1600 | 0.11 | 10 | 20.3 | 205 |
| | | | 60 | 28.59 | 0.075 | 2000 | | 8 | 24.9 | |
| JA0925H1S0N | S | | 50 | 19.7 | 0.041 | 1400 | | 10 | 15.1 | |
| | | | 60 | 23.19 | 0.053 | 1700 | | 8 | 21.9 | |
| JA0925H2B0N | B | 220 - 240 | 50 | 21.37 | 0.046 | 1500 | 0.05 | 10 | 16.3 | |
| | | | 60 | 25.78 | 0.059 | 1800 | | 8 | 24.7 | |
| JA0925H2S0N | S | | 50 | 18.71 | 0.037 | 1400 | | 10 | 16.3 | |
| | | | 60 | 22.56 | 0.049 | 1700 | | 8 | 20.7 | |

Specifications subject to change without notice

