

# DC AXIAL FAN

JAMICON®

92X92X38 mm

UF0938-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

## SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF0938B1U	B	12	10.2~13.8	156.04	2.941	11000	3.20	38.40	4.0	68.8	258
UF0938B1S	B			143.00	2.420	10000	2.45	29.40	3.0	65.3	
UF0938B1H	B			127.76	1.956	9000	1.75	21.00	2.3	63.9	
UF0938B1M	B			111.25	1.553	8000	1.25	15.00	1.8	60.8	
UF0938B1L	B			99.69	1.241	7000	0.90	10.80	1.3	58.4	
UF0938B2T	B	24	20.4~27.6	171.10	3.500	12000	2.35	56.40	3.0	71.4	
UF0938B2U	B			156.04	2.941	11000	1.55	37.20	2.0	68.8	
UF0938B2S	B			143.00	2.420	10000	1.15	27.60	1.5	65.3	
UF0938B2H	B			127.76	1.956	9000	0.85	20.40	1.2	63.9	
UF0938B2M	B			111.25	1.553	8000	0.60	14.40	0.9	60.8	
UF0938B2L	B	48	40.8~55.2	99.69	1.241	7000	0.45	10.80	0.7	58.4	
UF0938B4T	B			171.10	3.500	12000	0.95	45.60	1.5	71.4	
UF0938B4U	B			156.04	2.941	11000	0.80	38.40	1.2	68.8	
UF0938B4S	B			143.00	2.420	10000	0.60	28.80	1.0	65.3	
UF0938B4H	B			127.76	1.956	9000	0.42	20.20	0.8	63.9	
UF0938B4M	B	48	40.8~55.2	111.25	1.553	8000	0.38	18.20	0.6	60.8	
UF0938B4L	B			99.69	1.241	7000	0.22	10.60	0.4	58.4	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

