

DC AXIAL FAN

JAMICON®

120X120X25 mm

KF1225-SL Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF1225-1SR02	Dual Ball	12	10.2 ~13.8	86.65	0.143	2600	0.30	3.60	0.35	37.6	118
KF1225-1HR02	B,H,S			74.25	0.111	2200	0.30	3.60	0.35	32.7	
KF1225-1M-02	B,H,S			59.78	0.076	1800	0.19	2.28	0.20	28.3	
KF1225-1L-02	B,H,S			46.51	0.053	1500	0.13	1.56	0.14	23.0	
KF1225-1E-02	B,H,S			41.37	0.038	1200	0.07	0.84	0.09	18.8	
KF1225-1V-02	B,H,S			39.75	0.030	1000	0.06	0.72	0.07	15.3	
KF1225-2SR02	Dual Ball	24	20.4 ~27.6	86.65	0.143	2600	0.20	4.80	0.20	37.6	
KF1225-2HR02	B,H,S			74.25	0.111	2200	0.18	4.32	0.20	32.7	
KF1225-2M-02	B,H,S			59.78	0.076	1800	0.12	2.88	0.13	28.3	
KF1225-2L-02	B,H,S			46.51	0.053	1500	0.08	1.92	0.09	23.0	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

