

DC AXIAL FAN

JAMICON®

120X120X38 mm

UF1238-11 Series



- Frame : Plastic Material UL 94V-0
- Impeller : Plastic Material UL 94V-0
- Speed Range : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
UF1238B1T	B	12	10.2~13.8	261.4	1.488	6700	3.35	40.20	4.0	66.5	361
UF1238B1U	B			232.8	1.224	6000	2.40	28.80	3.0	64.4	
UF1238B1S	B			189.5	0.974	5000	1.28	15.36	1.8	60.1	
UF1238B1H	B			170.5	0.805	4500	0.97	11.64	1.4	57.5	
UF1238B2X	B	24	20.4~27.6	287.6	1.736	7500	2.30	55.20	2.8	69.5	
UF1238B2T	B			261.4	1.488	6700	1.53	36.72	2.0	66.5	
UF1238B2U	B			232.8	1.224	6000	1.05	25.20	1.5	64.4	
UF1238B2S	B			189.5	0.974	5000	0.65	15.60	0.9	60.1	
UF1238B2H	B	48	40.8~55.2	170.5	0.805	4500	0.45	10.80	0.7	57.5	
UF1238B4X	B			287.6	1.736	7500	1.10	52.80	1.4	69.5	
UF1238B4T	B			261.4	1.488	6700	0.80	38.40	1.0	66.5	
UF1238B4U	B			232.8	1.224	6000	0.58	27.84	0.8	64.4	
UF1238B4S	B	48	40.8~55.2	189.5	0.974	5000	0.32	15.36	0.6	60.1	
UF1238B4H	B			170.5	0.805	4500	0.25	12.00	0.4	57.5	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

